

Hikvision DS-3WAP621E-SI wireless access point 3000 Mbit/s White Power over Ethernet (PoE)



Brand : Hikvision

Product code: DS-3WAP621E-SI

Product name : DS-3WAP621E-SI

- 2 Gigabit LAN Ports with 1 PoE Input
 - 802.11ax Wi-Fi 6 2975 Mbps
 - 86 mm Wall Junction Box for Easy Installation
 - 70+ Concurrent User Connections
 - Auto RF Optimization
 - Support Intelligent Fast Roaming
- Wi-Fi 6, 2.4 GHz (575 Mbps) / 5 GHz (2400 Mbps), 86 x 86 x 44.4 mm

[Hikvision DS-3WAP621E-SI wireless access point 3000 Mbit/s White Power over Ethernet \(PoE\):](#)

What we offer

Surveillance data travels a long and winding road to get to the screens in front of you. And just as they were captured, they need to be presented to the viewers without losing any details. Depending on the details of your installation, many types of obstacles and interference can stand in the way of critical transmission. To make the journey safe and smooth, your data needs a little help.

Hikvision's transmission product lines offer a wide range of equipment and accessories that do more than just create a complete security system – they transform it into a system that boosts high efficiency and optimal performance.

Features		Power	
2.4 GHz *	✓	Power consumption (max)	13 W
5 GHz *	✓	Design	
6 GHz *	✗	Placement *	In-wall
Maximum data transfer rate *	3000 Mbit/s	Product colour *	White
Maximum data transfer rate (2.4 GHz)	575 Mbit/s	Reset button	✓
Maximum data transfer rate (5 GHz)	2400 Mbit/s	LED indicators	✓
Ethernet LAN data rates	10,100,1000 Mbit/s	Antenna	
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n	Antenna type *	Internal
Cabling technology	10/100/1000Base-T(X)	Antenna direction type	Omni-directional
Number of users	256 user(s)	Weight & dimensions	
Security		Width	86 mm
Security algorithms *	WPA-PSK, WPA2-PSK	Depth	44.4 mm
Number of SSID supported	8	Height	86 mm
Management features		Weight	170 g
Web-based management	✓	Packaging content	
Firmware upgradeable	✓	Number of products included	1 pc(s)
Ports & interfaces		Operational conditions	
Ethernet LAN (RJ-45) ports *	2	Operating relative humidity (H-H)	5 - 95%
Power		Operating temperature (T-T)	0 - 40 °C
Power over Ethernet (PoE) *	✓	Storage temperature (T-T)	-40 - 70 °C
		Storage relative humidity (H-H)	5 - 95%



6942160449555

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 19-AUG-2024. Prints or copies of Information are only valid on the printed Publication date