

# Hikvision DS-3WAP622E-SI wireless access point 2400 Mbit/s White Power over Ethernet (PoE)



**Brand :** Hikvision

**Product code:** DS-3WAP622E-SI

**Product name :** DS-3WAP622E-SI

- 1 x 2.5 Gigabit Port with PoE Input
- 802.11ax Wi-Fi 6 2975 Mbps
- 100+ Concurrent User Connections
- Auto RF Optimization
- Support Intelligent Fast Roaming
- Wi-Fi 6 3000M Ceiling Access Point

Hikvision DS-3WAP622E-SI. 2.4 GHz, 5 GHz, Maximum data transfer rate: 2400 Mbit/s, Ethernet LAN data rates: 2500 Mbit/s. Power over Ethernet (PoE). Product colour: White. Power consumption (max): 13.5 W

Features		Design	
2.4 GHz *	✓	Placement *	Ceiling, Desk, Wall
5 GHz *	✓	Product colour *	White
6 GHz *	✗	Reset button	✓
Maximum data transfer rate *	2400 Mbit/s	LED indicators	✓
Maximum data transfer rate (2.4 GHz)	575 Mbit/s	Certification	CE-EMC (EN 55032: 2015+A11: 2020, EN IEC 61000-3-2: 2019, EN 61000-3-3: 2013+A1: 2019, EN 50130-4: 2011+A1: 2014, EN 55035: 2017+A11: 2020) CB (AMD1:2009, AMD2:2013, IEC 62368-1: 2014 (Second Edition), CE-LVD (EN 62368-1: 2014+A11: 2017),UL (UL 60950-1) CE-RoHS (2011/65/EU),WEEE (2012/19/EU),Reach (Regulation (EC) No.1907/2006) EN 301 893,EN 300 440,EN 62311,EN 301 489-3,EN 301 489-17
Maximum data transfer rate (5 GHz)	2400 Mbit/s		
Ethernet LAN data rates	2500 Mbit/s		
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.3af, IEEE 802.3at		
MIMO	✓		
MIMO type	Multi User MIMO		
Spread spectrum method	DSSS, OFDM		
Security		Antenna	
Number of SSID supported	8	Antenna type *	Internal
Blacklist	✓	Antenna direction type	Omni-directional
Whitelist	✓	Antennas quantity	2
Protocols		Antenna gain level (max)	4 dBi
Supported network protocols	WAP-PSK,WAP2-PSK,WPA-WAP2-PSK	Weight & dimensions	
Management features		Width	220 mm
Firmware upgradeable	✓	Depth	39 mm
Ports & interfaces		Height	220 mm
Ethernet LAN (RJ-45) ports *	1	Weight	380 g
Power		Packaging content	
Power over Ethernet (PoE) *	✓	Quick start guide	✓
Output voltage	12 DC	Operational conditions	
Output current	1.5 A	Operating relative humidity (H-H)	5 - 95%
Power consumption (max)	13.5 W	Operating temperature (T-T)	0 - 45 °C
		Storage temperature (T-T)	-40 - 70 °C
		Storage relative humidity (H-H)	5 - 95%

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 23-AUG-2024. Prints or copies of Information are only valid on the printed Publication date