



Power over Ethernet Injector

GS-POE15W-MG/GS-POE30W-MG/GS-POE60W-MG

GS-POE15W-MG, GS-POE30W-MG, and GS-POE60W-MG are plug-and-play PoE Injectors, which provide power to Grandstream's PoE powered devices, such as GWN series Wi-Fi Access Points, IP phones, and more. They comply with IEEE 802.3af/at/bt standards. GS-POE15W-MG and GS-POE30W-MG have 2x 2.5G network ports and GS-POE60W-MG has 2x10G network ports and all models include a built-in power adapter with 1.2m AC cable.

	GS-POE15W-MG	GS-POE30W-MG	GS-POE60W-MG
Standards	IEEE 802.3 af	IEEE 802.3 af/at	IEEE 802.3 af/at/bt
Interface Ports	1xAC power Jack 1x2.5Gbps RJ45 LAN IN, 1x2.5Gbps RJ45 LAN OUT with PoE		1xAC power Jack 1x10G RJ45, LAN IN 1x10G RJ45, LAN OUT with PoE
Input Voltage	100~240VAC, 50/60Hz		
Output Voltage	54VDC 1,2 +; 3,6 -		54VDC 1,2/4,5 +;3,6/7,8 -
PoE Output Power	20W	30.2W	60W
LED	Power On: Blue PoE Load: Purple		
Environmental	Operation: 0°C to 45°C Storage: -10°C to 60°C Humidity: 10% to 90% Non-condensing		
Dimension (without Cable)	Unit: 140.55mm x 60.3mm x 35.4mm Entire Package: 225mm x 130.5mm x 46mm		
Weight	Unit: 175g Entire Package: 400g	Unit: 175g Entire Package: 400g	Unit: 240g Entire Package: 465g
Package Content	GS-POE15W-MG, 1.2m AC Cable, Quick Installation Guide	GS-POE30W-MG, 1.2m AC Cable, Quick Installation Guide	GS-POE60W-MG, 1.2m AC Cable, Quick Installation Guide
Compliance	FCC, CE, RCM, IC		