



# Enterprise Layer 2++ Managed Network Switches

## GWN7800 Pro Series

The GWN7800 Pro Series are layer 2++ managed network switches that allow small-to-medium enterprises to build scalable, secure, and high-performance business networks that are fully manageable. This Series provides high-speed SFP or SFP+ ports and Gigabit Ethernet ports on all models to support demanding business networks and offer switching capabilities up to 216Gbps. The GWN7800 Pro Series includes an advanced VLAN for flexible and sophisticated network traffic segmentation, advanced QoS for prioritization of network traffic, IGMP/MLD Snooping for network performance optimization, and comprehensive security capabilities against potential attacks. The PoE-capable models provide smart dynamic PoE output to power IP phones, IP cameras, Wi-Fi access points and other PoE endpoints. The GWN7800 Pro Series supports a variety of free and flexible management options, including cloud management with GDMS Networking, on-premise software management with GWN Manager, the embedded controller in their web user interface, GWN Series Routers, and command-line interface (CLI). By providing high-speed SFP and SFP+ ports, advanced control and segmentation of network traffic, powerful security protection, and flexible management options, the GWN7800 Pro Series are ideal for small to medium enterprises.



### Gigabit

8/16/24/48 Gigabit Ethernet ports with 2 SFP, 2 SFP+, or 6 SFP+ ports



### PoE

Smart power control to support dynamic PoE/PoE+/PoE++ (on select models) power allocation per port for the PoE-capable models



Supports deployment in IPv6 and IPv4 networks



ARP Inspection, IP Source Guard, DoS protection, port security & DHCP snooping



Flexible management options include the controller embedded in their WebUI, GDMS Networking (cloud), GWN Manager (software), GWN Series Routers, and CLI



Built-in QoS allows for prioritization of network traffic

# Hardware Specifications

	GWN7801P Pro	GWN7802P Pro	GWN7803 Pro	GWN7803PL Pro	GWN7803PH Pro	GWN7806PL Pro	GWN7806PH Pro
<b>Interfaces</b>							
<b>Gigabit Ethernet Ports</b>	8	16	24		48		
<b>SFP/SFP+ Ports</b>	2x 2.5G SFP	2x SFP+			6x SFP+		
<b>Maximum Amount of Supported Modules</b>	SM-10G: 2 MM-10G: 2 RJ45-10G: 2				SM-10G: 6 MM-10G: 6 RJ45-10G: 3 <i>*Note: RJ45-10G modules must be interval inserted</i>		
<b>MGMT Ports</b>	1x Console port						
<b>Auxiliary Ports</b>	1x Reset Pinhole						
<b>LEDs</b>							
<b>System LEDs</b>	1x tri-color LED for device tracking and status indication						
<b>Power Supply LEDs</b>	/	2x green-color LEDs for per power supply PWR&RPS		/	2x green-color LEDs for per power supply PWR&RPS		
<b>Data Transferring LEDs</b>	10x green-color LEDs	18x green-color LEDs	26x green-color LEDs			54x green-color LEDs	
<b>PoE Supply LEDs</b>	8x yellow-color LEDs	16x yellow-color LEDs	/	24x yellow-color LEDs		48x yellow-color LEDs	
<b>System</b>							
<b>Flash</b>	32MB Nor Flash					8MB Nor Flash, 128MB Nand Flash	
<b>RAM</b>	128MB RAM	256MB RAM			512MB RAM		
<b>CPU</b>	Single-core, MIPS interAptive™ 1GHz					Dual-core, MIPS interAptive™ 1GHz	
<b>Forwarding Mode</b>	Store-and-forward						
<b>Total non-blocking throughput</b>	13Gbps	36Gbps	44Gbps		108Gbps		
<b>Switching Capability</b>	26Gbps	72Gbps	88Gbps		216Gbps		
<b>Forwarding Rate</b>	19.344Mpps	53.568Mpps	65.472Mpps		160.704Mpps		
<b>Packet Buffer</b>	8.4Mb						
<b>Network Latency</b>	<4μs	<4μs	<4μs	<4μs	<4μs	<4μs	<4μs
<b>Power Supply</b>							
<b>Power Supply</b>	100-240V~ 50/60Hz						
<b>Redundant Power Supply</b>	/	1+1 External RPS, One by default		/	1+1 External RPS, One by default		
<b>External Redundant Power Supply (RPS)</b>	/	30W		/	460W	460W	800W
<b>Max Power Consumption</b>	9.5W 145.5W(PoE120W)	21.8W 294.4W(PoE 250W)	21.4W	27.5W 299.2W(PoE 250W)	30.5W 471.4W(PoE 400W)	65.4W 509.3W(PoE 400W)	68.0W 870.9W(PoE 800W)
<b>Max Output Power</b>	145.5W	294.4W	21.4W	299.2W	471.4W	509.3W	870.9W
<b>PoE</b>							
<b>PoE Standards</b>	IEEE 802.3af/at	IEEE 802.3af/at/bt	/	IEEE 802.3af/at	IEEE 802.3af/at/bt	IEEE 802.3af/at	IEEE 802.3af/at/bt
<b># of PoE Ports</b>	8	16	/	24		48	
<b>Max Output Power per PoE Port</b>	30W	60W	/	30W	60W	30W	60W
<b>Max Total PoE Output Power</b>	120W	250W	/	250W	400W	400W	800W

	GWN7801P Pro	GWN7802P Pro	GWN7803 Pro	GWN7803PL Pro	GWN7803PH Pro	GWN7806PL Pro	GWN7806PH Pro
<b>Physical</b>							
<b>Unit Dimension</b>	330mm(L) × 175mm(W) × 44mm(H)	440mm(L) × 200mm(W) × 44mm(H)			440mm(L) × 300mm(W) × 44mm(H)		
<b>Unit Weight</b>	1.77kg	2.9kg	2.5kg	3.06kg	4.15kg	5.05kg	5.3kg
<b>Mounting</b>	Desktop, Wall-Mount, or Rack-Mount (rack-mounting kits included)				Desktop, or Rack-Mount (rack-mounting kits included)		
<b>Package Content</b>	1x Switch 1x 25cm Ground Cable 4x Rubber Footpads 1x Power Cord Anti-Trip 8x Screws (KM3*6) 1x 1.2m(10A) AC Cable 1x Simplified Quick Installation Guide 1x Regulatory Paper						
	1x Extended Rack-Mounting Kits	2x Rack-Mounting Kits					
<b>Environmental</b>							
<b>Temperature</b>	Operation: 0°C to 45°C Storage: -10°C to 60°C						
<b>Humidity</b>	Operation: 10% to 90% RH(Non-condensing) Storage: 5% to 95% RH(Non-condensing)						
<b>MTBF</b>	70,000H						
<b>Fan</b>	/	2	/	2	3	4	
<b>CPU Monitoring</b>	Monitoring CPU usage, over-CPU usage alarming						
<b>Memory Usage</b>	Monitoring memory usage, over-memory usage alarming						
<b>Power Supply Monitoring</b>	Monitoring of power supply model and status Power supply failure alarming						
<b>Fan Monitoring</b>	Automatic speed adjustment Fan failure alarming						
<b>Temperature Monitoring</b>	Temperature monitoring, over-temperature alarming						
<b>Surge Protection</b>	± 6KV CM for power ± 4KV CM for network ports						
<b>ESD</b>	± 12KV for contact discharge						
<b>Compliance</b>							
<b>Compliance</b>	FCC, CE, RCM, IC						

## Software Specifications

	GWN7801P Pro	GWN7802P Pro	GWN7803 Pro	GWN7803PL Pro	GWN7803PH Pro	GWN7806PL Pro	GWN7806PH Pro
<b>Network Protocol</b>	IPv4, IPv6, IEEE 802.3, IEEE 802.3i, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3z, IEEE 802.3ae, IEEE 802.3az, IEEE 802.3ad, IEEE 802.3x, IEEE 802.3af/at/bt, IEEE 802.1p, IEEE 802.1Q, IEEE 802.1d, IEEE 802.1w, IEEE 802.1s, IEEE 802.1x						
<b>Stacking</b>	/					Yes, up to 8 devices	
<b>Switching</b>	<ul style="list-style-type: none"> <li>Jumbo frame (maximum length: 12288)</li> <li>4K VLANs, port-based VLAN, IEEE 802.1Q VLAN tagging</li> <li>QinQ</li> <li>MAC-based VLAN</li> <li>Protocol-based VLAN</li> <li>Voice VLAN including auto voice VLAN, tagged OUI and untagged OUI</li> <li>GVRP(pending)</li> <li>ERPS(pending)</li> </ul>						
	Spanning tree, support STP/RSTP/MSTP/PVST(+)/RPVST(+), 16 instances for MSTP/PVST(+)/RPVST(+)					Spanning tree, support STP/RSTP/MSTP/PVST(+)/RPVST(+), 64 instances for MSTP/PVST(+)/RPVST(+)	
	/					Private VLAN	
	16K MAC addresses including static, dynamic and filtering MAC address					32K MAC addresses including static, dynamic and filtering MAC address	
	Link aggregation, including static and LACP					Link aggregation, including static and LACP	
Up to max 8 LAG groups and up to 8 members per LAG group					Up to max 32 LAG groups and up to 8 members per LAG group		
<b>IP Service</b>	<ul style="list-style-type: none"> <li>DHCP client, DHCP server, DHCP relay and DHCP snooping</li> <li>DHCPv6 client and DHCPv6 snooping</li> <li>ND snooping</li> <li>DNS</li> </ul>						
	64 ARP/NDP, including static and dynamic ARP/NDP					1K ARP/NDP, including static and dynamic ARP/NDP	
	16 VLAN virtual interfaces with 9216 MTU					32 VLAN virtual interfaces with 9216 MTU	

	GWN7801P Pro	GWN7802P Pro	GWN7803 Pro	GWN7803PL Pro	GWN7803PH Pro	GWN7806PL Pro	GWN7806PH Pro
<b>IP Routing</b>	Policy routing (pending)						
	32(IPv4)/32(IPv6) static routes					1K(IPv4)/1K(IPv6) static routes	
<b>Multicast</b>	IGMP Snooping with IGMPv2 and IGMPv3, 256 IGMP Snooping groups	IGMP Snooping with IGMPv2 and IGMPv3, 384 IGMP Snooping groups				IGMP Snooping with IGMPv2 and IGMPv3, 640 IGMP Snooping groups	
	MLD Snooping with MLDv1 and MLDv2, 256 MLD Snooping groups	MLD Snooping with MLDv1 and MLDv2, 384 MLD Snooping groups				MLD Snooping with MLDv1 and MLDv2, 640 MLD Snooping groups	
<b>Pro AV</b>	/					Built-in SDVoE Controller	
	AES67, DANTE, NDI						
<b>QoS</b>	<ul style="list-style-type: none"> <li>• Port priority</li> <li>• Priority mapping, including 802.1p mapping, DSCP mapping and IP precedence mapping</li> <li>• Queue scheduling, including SP, WRR, WFQ, SP-WRR and SP-WFQ</li> <li>• Traffic shaping</li> <li>• Rate limit</li> </ul>						
<b>ACL</b>	128 ACL for Ethernet, IPv4 and IPv6 with 1.5K ACE					256 ACL for Ethernet, IPv4 and IPv6 with 4K ACE	
	<ul style="list-style-type: none"> <li>• MAC ACLs (hardware ACLs based on source MAC address, destination MAC address, optional Ethernet type, and time range)</li> <li>• IPv4 ACLs (hardware ACLs based on source IP address, destination IP address, and optional protocol type, and time range)</li> <li>• IPv6 ACLs (hardware ACLs based on source IPv6 address, destination IPv6 address, and optional protocol type, and time range)</li> <li>• Expert ACLs (hardware ACLs based on flexible combinations of the VLAN ID, Ethernet type, MAC address, IP address, protocol type, and time range) (TBD)</li> <li>• Customized ACLs (ACL80) (TBD)</li> <li>• ACL redirection</li> <li>• ACL advanced settings, including statistics, mirror, priority mapping, and rate limit</li> <li>• ACL binding, including port and VLAN</li> </ul>						
<b>Security</b>	<ul style="list-style-type: none"> <li>• User hierarchical management and password protection, HTTPS, SSH, Telnet</li> <li>• Identity authentication, including 802.1X and MAC authentication</li> <li>• AAA authentication, including RADIUS, TACACS</li> <li>• Storm control</li> <li>• Port isolation</li> <li>• Port security, sticky MAC address, filtering invalid MAC addresses</li> <li>• IP/IPv6 source guard, DoS attack prevention, ARP inspection, CPU protection</li> <li>• Loop protection, including port loopback detection, BPDU protection, root protection, and loopback protection</li> <li>• Kensington Security Slot (Kensington Lock) support</li> <li>• Firmware signature</li> </ul>						
<b>Reliability</b>	<ul style="list-style-type: none"> <li>• Power supply modules in 1+1 redundancy mode</li> <li>• Stack intelligent upgrade</li> </ul>						
<b>Maintenance</b>	<ul style="list-style-type: none"> <li>• NTP</li> <li>• 1588v2 TC for precise time (pending)</li> <li>• CPU and memory monitoring</li> <li>• Fault detection and alarm for power supply and fan</li> <li>• SNMP including SNMPv1, SNMPv2c, SNMPv3</li> <li>• RMON including history groups, event groups, alarm groups, and statistics groups</li> <li>• LLDP&amp;LLDP-MED</li> <li>• Backup and restore</li> <li>• Syslog</li> <li>• Diagnostics including Ping, traceroute, Ping watchdog, mirror including SPAN and RSPAN, UDLD(TBD), copper test, fiber module, and one-click debugging</li> <li>• sFlow (pending)</li> <li>• Upgrade via FTPS/ TFTP/ HTTP/ HTTPS or local upload, mass provisioning using DHCP Option/ TR-069 (pending)/ GDMS Networking/ GWN Manager/ GWN series routers</li> </ul>						
<b>Management Platform</b>	<ul style="list-style-type: none"> <li>• Local Web GUI: embedded controller</li> <li>• GDMS Networking: free cloud management platform for unlimited GWN7800 Pro series switches</li> <li>• GWN Manager: premise-based software controller</li> <li>• GWN APP: integrated GDMS Networking and GWN Manager to manage GWN7800 Pro series switches via the APP</li> <li>• Management Protocol: SNMP, RMON, TR-069 (pending)</li> </ul>						

# Features & Benefits

## Powerful Business Processing Capabilities

- Static routing routes data communication between different network segments. Simpler, more efficient and more reliable.
- DHCP Server and Relay assigns IP addresses to hosts on the network.
- GVRP (pending) provides VLAN dynamic distribution, registration and attribute propagation, reducing manual configuration and ensuring the accuracy of the configuration.
- QoS, including Port Priority, Priority Mapping, Queue Scheduling, Traffic Shaping and Rate Limit.
- ACL filters data packets by configuring matching rules, processing operations and time schedules, and providing flexible security access control policies.
- IGMP Snooping and MLD Snooping to support multi-terminal HD video surveillance and video conferencing.
- IPv6 supports network transitions from IPv4 to IPv6.
- 1588v2 TC (pending) provides high-precision time synchronization between network devices, improving security while reducing costs in comparison to GPS time synchronization.
- Stacking provides powerful network expansion capabilities. By adding member devices, you can easily expand the number of ports, bandwidth and processing capacity of the stacking system.
- Built-in SDVoE Controller integrates monitoring, control and configuration to achieve high-fidelity, low-latency audio and video signal transmission.
- SDVoE technology allows high-definition video and audio signals to be transmitted over Ethernet, ideal for professional audio and video applications. SDVoE provides low latency and high bandwidth transmissions.
- By combining SDVoE encoders, decoders and controllers, the GWN7800 Series supports multiple-TV setups and multi-view systems.
- Pro AV Solutions - The GWN7800 Series delivers high-quality, low-latency audio and video processing, transmission, and display for enterprises, academia, entertainment, media, retail and more. This ensures reliable, flexible and engaging audiovisual experiences.

## Advanced Security Protection

- Static MAC tables and dynamic MAC tables allow data transmission, and MAC table filtering protects against network attacks.
- Packet filtering based on binding of IP address, MAC address, VLAN and port
- Dynamic ARP Inspection protects against ARP spoofing and ARP flooding attacks including gateway spoofing and man-in-the middle attacks that are common in LAN environments.
- IP/IPv6 Source Guard prevents illegal address spoofing including IP(v6)/MAC/VLAN spoofing and IP(v6)/VLAN spoofing.
- DoS Attack Defense prevents Land Attacks, Smurf Attacks, TCP SYN Attacks, Ping Flooding and more.
- 802.1X, MAC, RADIUS, AAA, and TACACS+ authentications provide authentication LAN devices.
- With port security, when the number of MAC addresses learned by a port reaches the maximum number, it will be set to error-down status automatically to stop learning and prevent MAC address attacks while controlling the network traffic of the port.
- With DHCP/DHCPv6 Snooping, only DHCP/DHCPv6 packets from trusted ports are allowed to keep the enterprise DHCP/DHCPv6 environment safe.

## Enhanced Reliability

- Redundant Power Supplies (RPS) and External redundant power modules (optional) ensure stable and reliable continuous usage.
- Supports fault detection and includes an alarm for the power supply and fan. The GWN7800 Series can automatically adjust the fan speed based on temperature changes to better adapt to the environment.
- Provides multiple levels of device protection, including overcurrent protection, overvoltage protection, overheat technology and surge protection.
- Dual boot of hardware level uses two FLASH chips to store boot software (system boot program), providing hardware level boot redundancy and backup while avoiding FLASH chip failures.(GWN7806PL/GWN7806PH Pro only)
- Dual system file redundancy and backup ensures quick startup and high-performance operation of the system while improving the stability of the device.

- STP/RSTP/MSTP guarantees fast convergence, improves fault tolerance, ensures network stability and provides link load balancing and redundancy.
- Compatible with PVST(+) / RPVST(+) for faster convergence, optimizing network performance through VLAN-based network load balancing.
- ERPS (pending) and loopback detection identifies and remove loops on the network.
- Link aggregation increases bandwidth while improving reliability and load balancing.
- Storm control prevents traffic interruptions caused by broadcast, multicast and certain unicast packets.
- Stacking supports the logical virtualization of up to 8 switches into one (GWN7806 Pro models). This improves device-level reliability through redundant backups between multiple member devices and link-level reliability through link aggregation functions across devices.
- AI Diagnostics (pending) to automatically analyze network traffic and device health through intelligent real-time monitoring of network status. This quickly locates and warns admins of potential faults, enhancing operational efficiency.

## PoE Capability

- Complies with IEEE 802.3af/at/bt standards to meet the PoE power supply requirements of security monitoring, audio and video conferencing, wireless signal coverage and more.
- User-defined time periods allow users to control the power supply of PoE ports on WebUI.
- Priority of PoE ports settings allow the GWN7800 Series to power ports based on priorities when power is insufficient.
- Maximum power allowed per port settings provide additional port control.
- Dynamic power negotiation via LLDP-MED

## Easy Management and Monitoring

- Management options include GDMS Networking (cloud), GWN Manager (on-premise software), WebUI (embedded controller), GWN Series Routers, CLI (Console, Telnet, SSH) and SNMP (v1/v2c/v3).
- Monitor CPU and memory usage to analyze network issues with tools such as Ping, Traceroute, UDLD (TBD) and Copper Test
- RMON, Syslog, traffic statistics and sFlow(pending) provide network optimization.
- LLDP and LLDP-MED provide automatic discovery, provisioning and management of endpoint devices.
- Stacking (only for GWN7806 Pro models) simplifies configuration and management, allowing multiple physical devices to become one virtual device. Users can log in to the stacking system through any member device to centrally configure and manage all devices in the stacked system.
- Scan the QR code on the device to quickly obtain device information and add it to the GWN App for remote management
- AI CLI provides intelligent prompts and corrections through natural language command inputs, reducing configuration difficulty, simplifying network management operations, and improving configuration efficiency.

## Power & Green Energy Efficiency

- Includes a high efficiency power supply module
- All Ethernet ports support EEE (Energy Efficient Ethernet), providing fast transitions between normal operation and low power states with low traffic and low power consumption.
- Intelligent control of fan speed based on the environmental temperature provides precise temperature control, energy saving and noise reduction.

## IPv4/IPv6 Dual Protocol Stack

- IPv4 routing protocol, including IPv4 unicast routing
- IPv6 routing protocols, including IPv6 unicast routing
- Supports an IPv4, IPv6 or IPv4/IPv6 hybrid environment
- Policy routing (pending) adjusts routing paths according to actual needs to meet network requirements and dynamically selects routing paths based on network load, thereby achieving load balancing.