



Accessories / RJ45 & Copper

UniFi Premium Patch Cable Outdoor



^ Overview

Available Lengths	End-to-end: 1, 2, 3, 5, 8, 12, 15 m (3.3, 6.6, 9.8, 16.4, 26.2, 39.8, 49.2 ft)
Available Colors	White, Black
Pack Options	Single Unit
Supported Data Rate	10G
Supported PoE Type	Up to PoE+++
Connector	(2) Frosted booted and shielding RJ45
Operating Environment	Outdoor

Cable

Jacket Diameter	1-8 m: 3.5 mm (0.14") 12-15 m: 3.9 mm (0.15")
Jacket Material	Thermoplastic elastomer (TPE)
Shielding Type	F/UTP
Conductor Type	Stranded copper
Conductor Wire Gage	1-8 m (3-26 ft): 34 AWG 12-15 m (39-49 ft): 32 AWG
Bend Radius	1-8 m: Min. 28 mm (1.1") 12-15 m: Min. 31 mm (1.22 ")

UV Resistance	ISO4892-2
Flame Rating	VW-1 (UL1581)
Standards	TIA/EIA-568-B.2 ISO/IEC 11801
Installation Temperature	-20 to 60°C (-4 to 140°F)
Ambient Storage Temperature	-40 to 85°C (-40 to 185°F)
Ambient Operating Temperature	-20 to 60°C (-4 to 140°F)