



Accessories / **Box Cables**

# UniFi Outdoor Cable



## ^ Overview

|                      |                                         |
|----------------------|-----------------------------------------|
| Length               | 305 m (1,000 ft)                        |
| Type                 | Category 5e                             |
| Color                | White                                   |
| Box Dimensions       | 330 x 330 x 340 mm<br>(13 x 13 x 13.4") |
| Box Weight           | 12.6 kg (27.78 lb)                      |
| UV Resistance        | ASTM G 151/154                          |
| Flame Rating         | VW-1 (UL1581)                           |
| Shielding Type       | STP                                     |
| Conductor Type       | Solid bare copper                       |
| Conductor Wire Gauge | 24 AWG                                  |

Cable

|                 |                               |
|-----------------|-------------------------------|
| Jacket Diameter | 6 mm (0.24")                  |
| Jacket Material | Thermoplastic elastomer (TPE) |
| Bend Radius     | Min. 24 mm (0.94")            |

|                        |   |
|------------------------|---|
| Anti-Crosstalk Divider | — |
|------------------------|---|

|         |   |
|---------|---|
| Ripcord | ✓ |
|---------|---|

|           |                                  |
|-----------|----------------------------------|
| Standards | TIA/EIA-568-B.2<br>ISO/IEC 11801 |
|-----------|----------------------------------|

|                          |                           |
|--------------------------|---------------------------|
| Installation Temperature | -20 to 60°C (-4 to 140°F) |
|--------------------------|---------------------------|

|                             |                            |
|-----------------------------|----------------------------|
| Ambient Storage Temperature | -30 to 75°C (-22 to 167°F) |
|-----------------------------|----------------------------|

|                               |                            |
|-------------------------------|----------------------------|
| Ambient Operating Temperature | -40 to 80°C (-40 to 176°F) |
|-------------------------------|----------------------------|

|                |   |
|----------------|---|
| NDAA Compliant | ✓ |
|----------------|---|