



Accessories / RJ45 & Copper

UniFi Premium Patch Cable



^ Overview

Available Lengths	End-to-end: 0.15, 0.3, 1, 2, 3, 5, 8, 12, 15 m (0.5, 1, 3.3, 6.6, 9.8, 16.4, 26.2, 39.8, 49.2 ft)
Available Colors	White
Pack Options	Single Unit 24-Pack (0.15 m)
Supported Data Rate	10G
Supported PoE Type	Up to PoE+++
Connector	(2) Translucent booted and shielding RJ45
Operating Environment	Indoor

Cable

Jacket Diameter	0.15-8 m: 3 mm (0.11") 12-15 m: 3.3 mm (0.13")
Jacket Material	Thermoplastic elastomer (TPE) & Braided
Shielding Type	UTP
Conductor Type	Stranded copper
Conductor Wire Gage	1-8 m (3-26 ft): 34 AWG 12-15 m (39-49 ft): 32 AWG
Bend Radius	1-8 m: Min. 24 mm (0.94 ") 12-15 m: Min. 27 mm (1.06 ")

Flame Rating	VW-1 (UL1581)
Standards	TIA/EIA-568-B.2 ISO/IEC 11801
Installation Temperature	-20 to 60°C (-4 to 140°F)
Ambient Storage Temperature	-20 to 75°C (-4 to 167°F)
Ambient Operating Temperature	-20 to 60°C (-4 to 140°F)