



Accessories / PoE & Power

2.5G PoE+ Adapter (30W)



Dimensions	93 x 62 x 35 mm (3.7 x 2.4 x 1.4")
Weight	156 g (5.5 oz)
Output voltage	48V DC @ 0.65A
LAN activity indicator	No
Gigabit LAN port	Yes, up to 2.5 GbE
Remote reset capability	No
Reset button	No
Rated voltage	100—240V AC @ 50/60Hz
Input current	0.75A max.
Inrush current	<150A peak @ 230V AC
Efficiency	>87%
Output ripple	1% max.
Switching frequency	65 kHz max.

Line regulation	≤ 1%
Load regulation	≤ 3%
2-pair powering	Pins 4, 5 (+) and 7, 8 (-)
4-pair powering	No
Data In / PoE	RJ45 shielded socket
Surge protection	Difference and common mode
Clamping protection	11V data, 60V power
Max. surge discharge	1500A (8/20 μs) power
Peak pulse current	36A (10/1000 μs) data
Shunt capacitance	<5 pF data
Response time	<1 ns
Ambient operating temperature	0 to 40° C (32 to 104° F)
Storage temperature	-30 to 70°C (-22 to 158° F)
Ambient operating humidity	10 to 95% noncondensing
Certifications	CE, FCC, IC, UL, UKCA, KC, CCC, RoHS
NDAA Compliant	Yes
Dimensions	93 x 62 x 35 mm (3.7 x 2.4 x 1.4")