



# UniFi / Bridging Device Bridge



## Mechanical

Dimensions 130 x 55 x 34 mm (5.1 x 2.2 x 1.3")

Weight 200 g (7.1 oz)

Enclosure material Polycarbonate

Mount material Polycarbonate

## Hardware

Management interface WiFi

Networking interface (1) GbE RJ45 port

PoE interface (1) Passive PoE output

Button (1) Factory-reset

LED (4) Blue: signal  
(1) White/blue: indicator

Power method 100—240V AC, 0.45A Max., 50/60 Hz

Max. power consumption AC input: 25W  
Excluding PoE output: 10W

Max. PoE wattage per port 15W

Supported voltage range 100—240V AC

WiFi standards 802.11a/n/ac

Max. TX power

2.4 GHz —

5 GHz 21 dBm

6 GHz —

MIMO

2.4 GHz —

5 GHz 2 x 2

6 GHz —

Max. data rate	
2.4 GHz	–
5 GHz	866.7 Mbps (BW80)
6 GHz	–
Antenna gain	
2.4 GHz	–
5 GHz	Internal antenna : 5 dBi / External omni antenna : 4 dBi
6 GHz	–
Antenna	(1) Internal antenna (1) RP-SMA connector for external omni-antenna
Mounting	Wall (Included)
Ambient operating temperature	-10 to 40° C (14 to 104° F)
Ambient operating humidity	5 to 95% noncondensing
Certifications	CE, FCC, IC

### Supported Data Rates

802.11a	6, 9, 12, 18, 24, 36, 48, 54 Mbps
802.11n	6.5 Mbps to 300 Mbps (MCS0 - MCS15, HT 20/40)
802.11ac	6.5 Mbps to 866.7 Mbps (MCS0 - MCS9 NSS1/2, VHT 20/40/80)

