



Camera Security / **Special Devices**

Entry Sensor



^ Overview

Dimensions

Device: 75.5 x 23.5x 22.5 mm
(3 x 0.93 x 0.89")
Magnet: 39 x 15.1 x 12.9 mm
(1.5 x 0.6 x 0.5")

Mounting

Adhesive and screw mount

UniFi Application Suite

Protect

✓

^ Performance

Connectivity SuperLink (Proprietary)

Operating Frequency

US	915.6-927.6 MHz
EU	865.1-869.5 MHz

Antenna Gain

SuperLink	0 dBi
-----------	-------

Max. TX Power

SuperLink	14 dBm
-----------	--------

Max. Range

SuperLink	2 km (1.2 mi) ⓘ
-----------	-----------------

Sensor Features

Reed Switch	✓
-------------	---

^ Hardware

Max. Power Consumption	27.7mW
Supported Voltage Range	3V
Power Method	Lithium battery CR123A
Battery Life	Up to 6 years
Weight	Device: 41 g (1.4 oz) Magnet: 22 g (0.8 oz)
Enclosure Material	Polycarbonate
Mount Material	Polycarbonate
Buttons	(1) Factory-reset (1) Function button (1) Tamper switch
LEDs	(1) Status: R/B/W (1) Signal: B/R
Ambient Operating Temperature	0 to 40° C (32 to 104° F)
Ambient Operating Humidity	10 to 90% noncondensing
Certifications	FCC, IC, CE
NDAA Compliant	✓

^ Software

Application Requirements

Web Application	UniFi Protect
Mobile App	UniFi Protect iOS™ and Android™

