



Camera Security / **Special Devices**

Environmental Sensor



^ Mechanical

Dimensions

Device: 53 x 49 x 23.5 mm
(2.1 x 1.9 x 0.9")
Mount: 41.3 x 36.6 x 3.1 mm
(1.6 x 1.4 x 0.1")

Weight

Device: 47.8 g (1.7 oz)
With mount: 70 g (2.5 oz)

Enclosure Material

Polycarbonate

Mount Material

Galvanized steel

Mounting

Adhesive, magnet and screw mount

Weatherproofing

IPX5

^ **Hardware**

Connectivity SuperLink (Proprietary)

Sensor Features

Temperature Sensor	✓
Humidity Sensor	✓
Ambient Light Sensor	✓
Water Sensor	✓ ⓘ
Other	3.5 mm AUX jack for water leak probe

Power Method Lithium battery CR123A

Battery Life Up to 6 years

Supported Voltage Range 3V

Max. Power Consumption 34.9mW

Antenna Gain

SuperLink	0 dBi
-----------	-------

Max. TX Power

SuperLink	14 dBm
-----------	--------

Operating Frequency

US	915.6–927.6 MHz
EU	865.1–869.5MHz

Max. Range

SuperLink	2 km (1.2 mi) ⓘ
-----------	-----------------

LEDs

(1) Status: R/B/W
(1) Signal: B/R

Buttons

(1) Factory-reset
(1) Function button

Ambient Operating Temperature

-20 to 40° C (-4 to 104° F)

Ambient Operating Humidity

10 to 90% noncondensing

NDAA Compliant

✓

Certifications

FCC, IC, CE

^ Software

Application Requirements

Web Application	UniFi Protect
Mobile App	UniFi Protect iOS™ and Android™

